



*At the Heart of Community*



## Rules & Restrictions (all types)

\*4" of gravel base is required, minimum CA-6, compacted.

All vegetation needs to be removed before the gravel base is installed.

\*All sidewalks shall be formed, with string lines in place at the time of inspection.

\*Sidewalks shall be a minimum of 36" wide for egress.

### Additional Concrete Rules & Restrictions

\*4" concrete minimum (Not 3½ ")

\*A 6 bag mix per cubic yard, with 3%-8% Air Entrainment

### Additional Paver Brick Rules & Restrictions

\*Submit specifications indicating the amount of base and bedding. Sidewalks require a minimum of 4-6" of base and 1-1½ " of bedding.

\*Edge restraints must be installed.

\*The base, bedding and bricks shall be compacted.

# Sidewalks

& Service Walks

## Locations

\*Walks may not be placed within any easements.

\*Call J.U.L.I.E. (800-892-0123) before digging.

## Costs

\$37.00 Plan Review Fee

\$52.00 Permit Fee

## Note:

\*If an inspector needs to return more than once for the same phase of any required inspection, a \$100.00 re-inspection fee for residential and a \$200.00 re-inspection fee for commercial projects will be required to be paid before the re-inspection takes place.

## What to Submit (all types)

\*Completed application.

\*1 copy of a Certified Plat of Survey showing all existing structures, accessories and flatwork with the proposed location of the sidewalk.

\*1 copy of a plan showing all required measurements for review.

\*Scope of work/proposal.

## Inspections

\*Inspections are scheduled for A.M. or P.M. Monday through Friday with 48 hours advance notice at 847-540-1696. Same day re-inspections are not available.

\*Base inspection is needed before laying any blacktop, concrete, or paver bricks.

### Concrete shall not be ordered or on site prior to completion of inspection.

\*Final inspection

I have read and reviewed these requirements.

\_\_\_\_\_  
Signature of Applicant

\_\_\_\_\_  
Date